



| Model | LX380L | LX500L | LW300 | LW400 | LX650 | LW600 | LX700 | LX900 | LX1500 | |
|---|--|--|---|---|---|--|---|---|---|--|
| | | | WIDESCREEN | WIDESCREEN | | WIDESCREEN | 4LCD | | | |
| Applications | Fixed Install | Fixed Install | Fixed Install | Fixed Install | Fixed Install/ Rental Staging | Fixed Install/ Rental Staging | High Brightness/ Large Venue | High Brightness/ Large Venue | High Brightness / Large Venue | |
| Lamp | Single Lamp | Single Lamp | Single Lamp | Single Lamp | Single Lamp | Dual Lamp | Single Lamp | Dual Lamp | Quad Lamp | |
| Technology | LCD 3 x 0.99" | LCD 3 x 1.3" | LCD 3 x 1.2" | LCD 3 x 0.75" | LCD 3 x 1.3" | 2 x 1.22" Inorganic LCD panels | LCD 3 x 1.3" | 3 x 1.8" Inorganic LCD panels | LCD 3 x 1.8" | |
| Format | 4:3 | 4:3 | 16:9 | 16:10 data / 16:9 Video | 4:3 | 17:10 PC / 16:9 Video Widescreen | 4:3 | 4:3 | 4:3 | |
| Brightness | 3800 | 5000 | 3000 | 4000 | 6500 | 6,000 | 7,000 | 9,000 | 15,000 | |
| Native Resolution | XGA - 1024 x 768 | XGA - 1024 x 768 | W-XGA - 1366 x 768 | W-XGA 1280 x 800 | XGA - 1024 x 768 | W-XGA 1366 x 800 | XGA - 1024 x 768 | XGA - 1024 x 768 | XGA - 1024 x 768 | |
| Weight - Kg | 8.7Kg | 8.7Kg | 7.9Kg | 7.2Kg | 11.4kgs | 27.6Kg | 11.4kgs | 27.6Kg | 36.5Kg | |
| Standard Inputs - Standard Outputs - | 3 x Data/ 3 x Video/ 2 x Audio Data & Audio | 3 x Data/ 3 x Video/ 2 x Audio Data & Audio | 3 x Data/ 3 x Video/ 2 x Audio Data & Audio | 2 x Data/ 3 x Video/ 2 x Audio Data & Audio | 3 x Data/ 3 x Video/ 2 x Audio Data & Audio | 1 x Data/ 2 x Video/ 1 x Audio tbc | 2 x Data/ 2 x Video/ 1 x Audio tbc | 2 x Data/ 2 x Video/ 1 x Audio tbc | 3 x Data/ 3 x Video Data | |
| Standard Lens | Body Only | Body Only | Body Only | 1.5 - 1.8:1 Lens Included | Body Only | Body Only | Body Only | Body Only | Body Only | |
| Lens Options 1 | 0.8:1 | 0.8:1 | 0.7:1 | 0.8:1 | 0.8:1 | 0.8:1 / 1.1:1 / 1.65:1 | 0.8:1, 1.2:1 | 0.8:1, 1.2:1 | 0.8:1 | |
| Lens Options 2 | 1.2 - 1.6:1 | 1.2 - 1.6:2 | 1.2 - 1.7:1 | 1.2 - 1.9:1 | 1.3 - 1.8:1 | 1.3-1.8:1 | 1.1 - 1.5:1, 1.3 - 1.8:1 | 1.1 - 1.5:1, 1.3 - 1.8:1 | 0.8:1, 1.2:1, 7.0:1 | |
| Lens Options 3 | 1.6 - 2.1:1 | 1.6 - 2.1:2 | 1.7 - 2.1:1 | 1.9 - 3.8:1 | 1.8-2.4:1 | 1.6-2.1:1 / 1.9-2.5:1 / 2.1-2.8:1 | 1.5-2.0:1, 2.0-2.6:1, 2.6-3.5:1 | 1.5-2.0:1, 2.0-2.6:1, 2.6-3.5:1 | 1.1-1.5:1, 1.5-2.0:1, 1.3-1.8:1 | |
| Lens Options 4 | 2.1 - 3.5:1 | 2.1 - 3.5:2 | 2.2 - 4.0:1 | 3.9 - 7.3:1 | 2.4-4.3:1 | 2.8-3.6:1 / 3.6-4.8:1 | 4.6-6.0:1, 6.3 - 9.0:1 | 4.6-6.0:1, 6.3 - 9.0:1 | 2.0-2.6:1, 2.6-3.5:1, 3.5-4.6:1 | |
| Lens Options 5 | 3.4 - 5.4:1 | 3.4 - 5.4:1 | 3.9 - 5.6:1 | - | 4.3-6.0:1 | 4.8-6.2:1 / 6.1-8.5:1 / 8.7-12.4:1 | 7.0:1 Fixed | 7.0:1 Fixed | 4.6-6.0:1 | |
| Lens Shift | U/D/L/R | U/D/L/R | U/D | U/D/L/R | U/D | U/D/L/R | U/D/L/R | U/D/L/R | U/D/L/R | |
| Keystone Correction | Yes +/- V | Yes +/- V | Yes +/- H&V | Yes +/- V Automatic | Yes +/- H&V | Yes +/- H&V | Yes +/- H&V | Yes +/- H&V | Yes +/- H&V | |
| Contrast Ratio | 1000:1 | 1000:1 | 1000:1 | 1000:1 | 2000:1 | 2000:1 | 2200:1 | 2000:1 | 2000:1 | |
| Lamp Life | 2000 Hours | 2000 Hours | 1500 Hours | 2000 Hours (3000 in Eco Mode) | 1500 Hours | 2000 Hours (3000 Eco) | 2000 Hours (3000 Eco) | 2000 Hours (3000 Eco) | 1000 Hours | |
| Noise Level | 35db | 35db | 38db | 37db (31 in Eco Mode) | 38db | 50db (47db Eco) | 38db | 50db (48db Eco) | 51db | |
| Lamp Warranty | 120 Days / 500 Hours | 120 Days / 500 Hours | 120 Days / 500 Hours | 120 Days / 500 Hours | 120 Days / 500 Hours | 120 Days / 500 Hours | 120 Days / 500 Hours | 120 Days / 500 Hours | 120 Days / 500 Hours | |
| Machine Warranty | 3 Years RTB | 3 Years RTB | 3 Years RTB | 3 Years RTB | 3 Years RTB | 3 Years RTB | 3 Years RTB | 3 Years RTB | 3 Years RTB | |
| Key Features - | DVI-D Input Easy Release System lens mount Fully Featured Remote Control Carrying handle and rugged cabinet | DVI-D Input Easy Release System lens mount Fully Featured Remote Control Carrying handle and rugged cabinet | 10-bit image processing FLC™ Fast Change lens mount Fully Featured Remote Control 3D Digital noise reduction | HDMI Input Carrying handle and rugged cabinet Dynamic iris control Audio Speakers 4W x2 New inorganic 3LCD light engine | 10-bit image processing Easy Release System lens mount Fully Featured Remote Control New inorganic 3LCD light engine | Twin Lamp Design with Failsafe FLC™ Fast Change lens mount Fully Featured Remote Control AutoFilter System New inorganic 3LCD light engine | Twin Lamp Design with Failsafe FLC™ Fast Change lens mount 10-bit image processing Fully Featured Remote Control AutoFilter System New inorganic 3LCD light engine | Twin Lamp Design with Failsafe FLC™ Fast Change lens mount 10-bit image processing Fully Featured Remote Control AutoFilter System New inorganic 3LCD light engine | Twin Lamp Design with Failsafe FLC™ Fast Change lens mount 10-bit image processing Fully Featured Remote Control AutoFilter System New inorganic 3LCD light engine | Quad Lamp Design with Failsafe 10-bit image processing Easy Release System lens mount Fully Featured Remote Control |

www.christiedigital.com

LCD MODELS